## NSN 5510-00-243-9146

Wood Crossarm - Page 1 of 1

Fiig: A173a0



View Online at https://aerobasegroup.com/nsn/5510-00-243-9146 **Treatment Type:** Preservative, tt-w-571 **Preservative Solution Type:** Creosote/pentachlorophenol **Species-grade And Grading Association:** Pine, southern ungraded unrecognized or douglas fir ungraded unrecognized **Moisture Content Retention Percentage:** 22.0 Width-location And Measuring Method: 4.250 inches specified **Measuring Method And Length:** 10.000 feet specified **Surface Condition Degree:** Surfaced four sides **Thickness-location And Measuring Method:** 3.250 inches specified **Typical Wood Products Use:** Line construction poles Service Usage: Utility **Special Features:** Bored with 18 pin holes (1-17/32 in. Dia) with 16 in. Center, 3 in. End and 8, 4, 4, 8, 8, 4, in. In. Side spacings, center bolt hole 0.687 in. Diameter and brace bolt holes 0.437 in. Dia, 43 in. Apart **Supplementary Features:** Edges chamfered or rounded, unit of issue ea **Specification Data:** 81349-mil-c-12436 government specification **Specification Or Standard:** 1 type Shelf Life: N/a **Unit Of Measure: Demilitarization:** No