

View Online at <https://aerobasegroup.com/nsn/5510-00-290-2102>

**Treatment Type:**

Preservative, tt-w-571

**Maximum Grain Slope:**

Any acceptable

**Preservative Solution Type:**

Coal-tar creosote or creosote coal-tar solution or creosote petroleum solution or pentachlorophenol in heavy petroleum solvent or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii

**Species-grade And Grading Association:**

Douglas-fir, coastal ungraded unrecognized or hemlock, western ungraded unrecognized or pine, lodgepole ungraded unrecognized or pine, southern ungraded unrecognized or pine, ponderosa ungraded unrecognized or pine, jack ungraded unrecognized or pine, norway ungraded unrecognized

**Measuring Method And Length:**

75.000 feet specified

**Surface Condition Degree:**

Clean peeled full length

**Typical Wood Products Use:**

Piles for cofferdams, false-work and other temporary construction preservative treated for land or fresh water use

**Minimum Circumference And Location:**

33.000 inches top and 19.000 inches butt

**Service Usage:**

Contact w/ground or in fresh water

**Supplementary Features:**

Tt-w-571, table 2, min circumferences iaw ansi/astm d-25 table 2, unit of issue-ea

**Specification Data:**

81348-mm-p-371 government specification

**Specification Or Standard:**

2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A173a0