NSN 5510-00-291-7886

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-291-7886

3	
Treatment Type:	
Preservative, tt-w-571	
Preservative Solution Type:	
Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or i	ii or pentachlorophenol
Species-grade And Grading Association:	
Douglas fir no. 1 west coast lumber inspection bureau or douglas fir no. 1 western wood products	association or hemlock, western no. 1
western wood products association or pine, southern no. 1 southern pine inspection bureau or re	dwood no. 1 redwood inspection service
Moisture Content Retention Percentage:	
19.0	
Width-location And Measuring Method:	
12.000 inches specified	
Measuring Method And Length:	
33.000 inches specified	
Surface Condition Degree:	
Rough-unsanded full length	
Thickness-location And Measuring Method:	
3.000 inches specified	
Typical Wood Products Use:	
Preservative treated stress rated joists and planks for use in cribbing for bailey type bridges	
Service Usage:	
Lumber or for use above ground	
Supplementary Features:	
Unit of issue-bf. Special purpose item	
Specification Data:	
81348-mm-I-751 government specification	
Specification Or Standard:	
lii table	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A173a0