Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-291-7886

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol

Species-grade And Grading Association:

Douglas fir no. 1 west coast lumber inspection bureau or douglas fir no. 1 western wood products association or hemlock, western no. 1 western wood products association or pine, southern no. 1 southern pine inspection bureau or redwood no. 1 redwood inspection service

Moisture Content Retention Percentage:

19.0

Width-location And Measuring Method:

12.000 inches specified

Measuring Method And Length:

33.000 inches specified

Surface Condition Degree:

Rough-unsanded full length

Thickness-location And Measuring Method:

3.000 inches specified

Typical Wood Products Use:

Preservative treated stress rated joists and planks for use in cribbing for bailey type bridges

Service Usage:

Lumber or for use above ground

Supplementary Features:

Unit of issue-bf. Special purpose item

Specification Data:

81348-mm-I-751 government specification

Specification Or Standard:

lii table

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A173a0