# NSN 5510-00-550-6845

Timber Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-550-6845

#### **Treatment Type:**

Preservative, tt-w-571

#### **Preservative Solution Type:**

Ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or coal-tar creosote or creosote coal-tar solution or creosote petroleum solution or pentachlorophenol in heavy petroleum solvent

#### **Species-grade And Grading Association:**

Douglas-fir, coastal no. 1 structural west coast lumber inspection bureau or douglas-fir, coastal no. 1 western wood products association or hemlock, western no. 1 structural west coast lumber inspection bureau or hemlock, western no. 1 western wood products association or larch no. 1 western wood products association or pine, southern no. 1 strimbers southern pine inspection bureau

#### Random Length:

10 ft and longer with a maximum of 10 pct to be 10 ft long and a min of 50 pct to e 14 ft and longer

### Width-location And Measuring Method:

12.000 inches specified

#### **Measuring Method And Length:**

10.000 feet random

#### **Surface Condition Degree:**

Rough-unsanded full length

#### **Thickness-location And Measuring Method:**

8.000 inches specified

#### **Typical Wood Products Use:**

Preservative treated beams, stringers, posts, timbers, columns and struts where creosote or oil-borne preservatives are required for use in fresh water ground contact

#### Service Usage:

Timbers and important structural members in contact with ground or fresh water

# **Supplementary Features:**

Tt-w-571, table 1; unit of issue bf

## **Specification Data:**

81348-mm-I-751 government specification

#### **Specification Or Standard:**

3 table

#### Shelf Life:

N/a

## **Unit Of Measure:**

# Demilitarization:

No

# Fiig:

A173a0