

View Online at <https://aerobasegroup.com/nsn/5510-00-550-6885>

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol in volatile solvent

Species-grade And Grading Association:

Any acceptable c select northeastern lumber manufacturers association or any acceptable c select northern hardwood and pine manufacturers association or any acceptable c and better siding west coast lumber inspection bureau or any acceptable c select western wood products association or pine, idaho white choice western wood products association or pine, southern c drop siding southern pine inspection bureau or redwood clear redwood inspection service

Moisture Content Retention Percentage:

15.0

Random Length:

4 ft and longer, with a maximum of 5 pct to be 4-7 ft and a min of 50 pct to be 12 ft and longer

Width-location And Measuring Method:

6.000 inches specified

Measuring Method And Length:

4.000 feet random

Surface Condition Degree:

Drop siding pattern 105 full length

Thickness-location And Measuring Method:

1.000 inches specified

Typical Wood Products Use:

Preservative treated high quality drop siding

Service Usage:

Lumber or for use above ground

Supplementary Features:

See tt-w-571, table 1, for acceptable species, tongued and grooved, unit of issue bf

Specification Data:

81348-mm-l-751 government specification

Specification Or Standard:

2 table

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A173a0