NSN 5510-00-551-5186

Board Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-551-5186

Species-grade And Grading Association:

Surface Condition Degree:

Thickness-location And Measuring Method:

Surfaced four sides

0.375 inches specified

Templates and patterns **Supplementary Features:** Unit of issue-board foot

Shelf Life:

Unit Of Measure:

Demilitarization:

N/a

No Fiig: A173a0

Typical Wood Products Use:

Basswood selects national hardwood lumber association or fir, balsam c select northeastern lumber manufacturers association or fir,
balsam c and better select northern hardwood and pine manufacturers association or pine, eastern white c select northeastern lumber
manufacturers association or pine, eastern white c and better select northern hardwood and pine manufacturers association or pine, idah
white choice western wood products association or pine, ponderosa c and better select western wood products association or pine,
ponderosa superior finish western wood products association or pine, sugar c and better select western wood products association or pine
sugar superior finish western wood products association or spruce, eastern c select northeastern lumber manufacturers association or
spruce, eastern c and better select northern hardwood and pine manufacturers association or spruce, engelmann c select western wood
products association or spruce, engelmann superior finish western wood products association or spruce, sitka c and better finish west
coast lumber inspection bureau
Moisture Content Retention Percentage:
15.0
Random Length:
8 ft and longer with a maximum of 5 pct to be 8 ft and a min of 50 pct to be 12 ft and longer
Width-location And Measuring Method:
6.000 inches specified
Measuring Method And Length:
8.000 feet random