NSN 5510-00-551-5186

Board Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-551-5186

Species-grade And Grading Association:

Surface Condition Degree:

Thickness-location And Measuring Method:

Surfaced four sides

0.375 inches specified

Templates and patterns **Supplementary Features:** Unit of issue-board foot

Shelf Life:

Unit Of Measure:

Demilitarization:

N/a

No Fiig: A173a0

Typical Wood Products Use:

| Basswood selects national hardwood lumber association or fir, balsam c select northeastern lumber manufacturers association or fir, |
|--|
| balsam c and better select northern hardwood and pine manufacturers association or pine, eastern white c select northeastern lumber |
| manufacturers association or pine, eastern white c and better select northern hardwood and pine manufacturers association or pine, idah |
| white choice western wood products association or pine, ponderosa c and better select western wood products association or pine, |
| ponderosa superior finish western wood products association or pine, sugar c and better select western wood products association or pine |
| sugar superior finish western wood products association or spruce, eastern c select northeastern lumber manufacturers association or |
| spruce, eastern c and better select northern hardwood and pine manufacturers association or spruce, engelmann c select western wood |
| products association or spruce, engelmann superior finish western wood products association or spruce, sitka c and better finish west |
| coast lumber inspection bureau |
| Moisture Content Retention Percentage: |
| 15.0 |
| Random Length: |
| 8 ft and longer with a maximum of 5 pct to be 8 ft and a min of 50 pct to be 12 ft and longer |
| Width-location And Measuring Method: |
| 6.000 inches specified |
| Measuring Method And Length: |
| 8.000 feet random |