NSN 5510-00-551-8686

Board Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-551-8686

Species-grade And Grading Association:

Any acceptable clear redwood inspection service or any acceptable d finish southern pine inspection bureau or any acceptable d finish west coast lumber inspection bureau or any acceptable d select northeastern lumber manufacturers association or any acceptable d select northern hardwood and pine manufacturers association or any acceptable d select western wood products association or any acceptable prime finish western wood products association or any acceptable quality western wood products association

Moisture Content Retention Percentage:

15.0

Random Length:

4 ft and longer with a maximum of 5 pct to be 4-7 ft, and a min of 50 pct to be 12 ft and longer

Width-location And Measuring Method:

10.000 inches specified

Measuring Method And Length:

4.000 feet random

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

1.000 inches specified

Typical Wood Products Use:

Good quality finish for cornice trim, door and window casing and cabinet work

Supplementary Features:

See rulerbooks for actual thk of select grades; unit of issue-bf

Specification Data:

81348-mm-I-751 government specification

Specification Or Standard:

I table

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A173a0