Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-551-9671

Species-grade And Grading Association:

Any acceptable c and better select northern hardwood and pine manufacturers association or any acceptable c finish southern pine inspection bureau or any acceptable c select northeastern lumber manufacturers association or any acceptable c select western wood products association or any acceptable clear redwood inspection service or any acceptable superior finish western wood products association or cedar, western c and better finish west coast lumber inspection bureau **Moisture Content Retention Percentage:**

15.0

Random Length:

4 ft and longer with a maximum of 5 pct to be 4-7 ft long with a min of 50 pct to be 12 ft and longer

Width-location And Measuring Method:

12.000 inches specified

Measuring Method And Length:

4.000 feet random

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

2.000 inches specified

Typical Wood Products Use:

Highest quality and most expensive finish lumber for interior trim, cabinet work, door and window trim

Supplementary Features:

See rule book for actual thk of select grades, unit of issue bf

Specification Data:

81348-mm-I-751 government specification

Specification Or Standard:

3 table

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A173a0