

View Online at <https://aerobasegroup.com/nsn/5510-00-551-9672>

**Species-grade And Grading Association:**

Any acceptable c and better select northern hardwood and pine manufacturers association or any acceptable c finish southern pine inspection bureau or any acceptable c select northeastern lumber manufacturers association or any acceptable c select western wood products association or any acceptable choice western wood products association or any acceptable clear redwood inspection service or any acceptable superior finish western wood products association or cedar, western c and better finish west coast lumber inspection bureau

**Moisture Content Retention Percentage:**

15.0

**Random Length:**

4 ft and longer with a maximum of 5 pct to be 4-7 ft lg and a min of 50 pct to be 12 ft or longer

**Width-location And Measuring Method:**

10.000 inches specified

**Measuring Method And Length:**

4.000 feet random

**Surface Condition Degree:**

Surfaced four sides

**Thickness-location And Measuring Method:**

2.000 inches specified

**Typical Wood Products Use:**

Highest quality and most expensive finish lumber for interior trim, cabinet work, door and window trim

**Supplementary Features:**

See rule book for actual thk of select grades, unit of issue bf

**Specification Data:**

81348-mm-l-751 government specification

**Specification Or Standard:**

3 table

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A173a0