NSN 5510-00-551-9868

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-551-9868

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol in light petroleum solvent or pentachlorophenol in volatile solvent

Species-grade And Grading Association:

Douglas-fir, coastal no. 1 west coast lumber inspection bureau or douglas-fir, south, interior no. 1 west coast lumber inspection bureau or hemlock, western no. 1 west coast lumber inspection bureau or larch no. 1 western wood products association or pine, eastern white no. 1 northern hardwood and pine manufacturers association or pine, idaho white no. 1 western wood products association or pine, jack no. 1 northern hardwood and pine manufacturers association or pine, lodgepole no. 1 western wood products association or pine, ponderosa no. 1 western wood products association or pine, norway no. 1 northern hardwood and pine manufacturers association or pine, southern no. 1 southern pine inspection bureau or pine, sugar no. 1 western wood products association or redwood no. 1 redwood inspection service

Moisture Content Retention Percentage:

19.0

Random Length:

6 ft and longer with a maximum of 10pct to be 6-9 ft and a min of 40 pct to be 14 ft and longer

Width-location And Measuring Method:

12.000 inches specified

Measuring Method And Length:

6.000 feet random

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

2.000 inches specified

Typical Wood Products Use:

Preservative treated high quality construction for above ground use for cleanliness and paintability

Service Usage:

Lumber and for use above ground

Supplementary Features:

Unit of issue-bf

Specification Data:

81348-mm-l-751 government specification

Specification Or Standard:

lii table

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A173a0