

View Online at <https://aerobasegroup.com/nsn/5510-00-551-9872>

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol in light petroleum solvent or pentachlorophenol in volatile solvent

Species-grade And Grading Association:

Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable construction northeastern lumber manufacturers association or any acceptable no. 1 northern hardwood and pine manufacturers association or any acceptable construction northern hardwood and pine manufacturers association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable construction west coast lumber inspection bureau or any acceptable no. 1 western wood products association or any acceptable construction western wood products association or pine, southern no. 1 southern pine inspection bureau or pine, southern construction southern pine inspection bureau or redwood no. 1 redwood inspection service or redwood construction redwood inspection service

Moisture Content Retention Percentage:

19.0

Random Length:

6 ft and longer with a maximum of 10 pct to be 6-9 ft and a min of 40 pct to be 14 ft and longer

Width-location And Measuring Method:

4.000 inches specified

Measuring Method And Length:

6.000 feet random

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

2.000 inches specified

Typical Wood Products Use:

Preservative treated high quality construction for above ground use for cleanliness and paintability

Service Usage:

Lumber and for use above ground

Supplementary Features:

See table i, tt-w-571 for acceptable species, unit of issue bf

Specification Data:

81348-mm-l-751 government specification

Specification Or Standard:

3 table

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A173a0