

View Online at <https://aerobasegroup.com/nsn/5510-00-551-9876>

**Treatment Type:**

Preservative, tt-w-571

**Preservative Solution Type:**

Ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or coal-tar creosote or creosote coal-tar solution or creosote petroleum solution or pentachlorophenol in heavy petroleum solvent

**Species-grade And Grading Association:**

Douglas-fir, coastal no. 1 structural west coast lumber inspection bureau or douglas-fir, coastal no. 1 western wood products association or hemlock, western no. 1 structural west coast lumber inspection bureau or hemlock, western no. 1 western wood products association or larch no. 1 western wood products association or pine, southern no. 1 sr timbers southern pine inspection bureau

**Random Length:**

10 ft and longer, with a maximum of 10 pct to be 10 ft long and a min of 50 pct to be 14 ft and longer

**Width-location And Measuring Method:**

6.000 inches specified

**Measuring Method And Length:**

10.000 feet random

**Surface Condition Degree:**

Rough-unsanded full length

**Thickness-location And Measuring Method:**

6.000 inches specified

**Typical Wood Products Use:**

Preservative treated beams, stringers, posts, timbers, columns and struts where creosote or oil-borne preservatives are required for use in fresh water ground contact

**Service Usage:**

Timbers and important structural members in contact with ground or fresh water

**Supplementary Features:**

Tt-w-572, table 1; unit of issue bf

**Specification Data:**

81348-mm-l-751 government specification

**Specification Or Standard:**

3 table

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A173a0