

View Online at <https://aerobasegroup.com/nsn/5510-00-554-7762>

**Treatment Type:**

Preservative, tt-w-571

**Preservative Solution Type:**

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol in light petroleum solvent or pentachlorophenol in volatile solvent

**Species-grade And Grading Association:**

Any acceptable no. 2 northeastern lumber manufacturers association or any acceptable no. 2 northern hardwood and pine manufacturers association or any acceptable no. 2 west coast lumber inspection bureau or any acceptable no. 2 western wood products association or pine, southern no. 2 southern pine inspection bureau or redwood no. 2 redwood inspection service

**Random Length:**

8 ft and longer with a maximum of 5 pct to be 8-9 ft and a min of 50 pct to be 14 ft and longer

**Width-location And Measuring Method:**

8.000 inches specified

**Measuring Method And Length:**

8.000 feet random

**Surface Condition Degree:**

Surfaced four sides

**Thickness-location And Measuring Method:**

4.000 inches specified

**Typical Wood Products Use:**

Preservative treated for heavy construction, rafters, decking, beams and stringers for above ground use where cleanliness and paintability required

**Service Usage:**

Lumber and for use above ground

**Supplementary Features:**

See table i it-w-571 for acceptable species. Unit of issue-bf

**Specification Data:**

81348-mm-l-751 government specification

**Specification Or Standard:**

3 table

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A173a0