Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-554-7764

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol in light petroleum solvent or pentachlorophenol in volatile solvent

Species-grade And Grading Association:

Any acceptable no. 2 northeastern lumber manufacturers association or any acceptable no. 2 northern hardwood and pine manufacturers association or any acceptable no. 2 west coast lumber inspection bureau or any acceptable no. 2 western wood products association or pine, southern no. 2 southern pine inspection bureau or redwood no. 2 redwood inspection service

Random Length:

8 ft and longer with a maximum of 5 pct to be 8-9 ft and a min of 50 pct to be 14 ft and longer

Width-location And Measuring Method:

12.000 inches specified

Measuring Method And Length:

8.000 feet random

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

4.000 inches specified

Typical Wood Products Use:

Preservative treated for heavy construction, rafters, decking, beams and stringers for above ground use where cleanliness and paintability required

Service Usage:

Lumber and for use above ground

Supplementary Features:

See table i tt-w-571 for acceptable species. Unit of issue-bf

Specification Data:

81348-mm-I-751 government specification

Specification Or Standard:

3 table

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A173a0