## NSN 5510-00-555-9059

Board Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-555-9059

## **Species-grade And Grading Association:**

Any acceptable c select northeastern lumber manufacturers association or any acceptable c and better select northern hardwood and pine manufacturers association or any acceptable c and better finish west coast lumber inspection bureau or any acceptable c select western wood products association or cedar, western a finish west coast lumber inspection bureau or pine, idaho white choice western wood products association or pine, southern c finish southern pine inspection bureau or redwood clear redwood inspection service

wood producted deconstation of any decoptable deponds initial wood producte deconstation of decay, western a limit wood order.
lumber inspection bureau or pine, idaho white choice western wood products association or pine, southern c finish southern pine
inspection bureau or redwood clear redwood inspection service
Moisture Content Retention Percentage:
15.0

## Random Length:

-----

R ft and longer, with a maximum of 5 pct to be 4-7 ft and a min of 50 pct to be 12 ft and longer

Width-location And Measuring Method:

10.000 inches specified

**Measuring Method And Length:** 

4.000 feet random

**Surface Condition Degree:** 

Surfaced four sides

**Thickness-location And Measuring Method:** 

1.500 inches specified

**Typical Wood Products Use:** 

High quality finish interior trim, cabinet work, casing, baseboard, door and window trim

**Supplementary Features:** 

See rulebook for actual thk of select grades. Unit of issue-bf

**Specification Data:** 

81348-mm-I-751 government specification

**Specification Or Standard:** 

1 table

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A173a0