Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-558-0426

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Coal-tar creosote or creosote coal-tar solution or creosote petroleum solution or pentachlorophenol in heavy petroleum solvent

Species-grade And Grading Association:

Douglas-fir, coastal no. 1 west coast lumber inspection bureau or douglas-fir, coastal no. 1 western wood products association or douglas-fir, south, interior no. 1 west coast lumber inspection bureau or douglas-fir, south, interior no. 1 western wood products association or hemlock, western no. 1 west coast lumber inspection bureau or hemlock, western no. 1 western wood products association or larch no. 1 western wood products association or pine, eastern white no. 1 northeastern lumber manufacturers association or pine, eastern white no. 1 northern hardwood and pine manufacturers association or pine, jack no. 1 northeastern lumber manufacturers association or pine, jack no. 1 northeastern lumber manufacturers association or pine, lodgepole no. 1 western wood products association or pine, norway no. 1 northeastern lumber manufacturers association or pine, norway no. 1 northeastern lumber manufacturers association or pine, norway no. 1 northeastern lumber manufacturers association or pine, norway no. 1 northeastern lumber manufacturers association or pine, norway no. 1 northeastern lumber manufacturers association or pine, norway no. 1 northern hardwood and pine manufacturers association or pine, sugar no. 1 western wood products association or pine, southern no. 1 southern pine inspection bureau or pine, sugar no. 1 western wood products association or redwood no. 1 redwood inspection service

Random Length:

8 ft and longer with a maximum of 5pct to be 8-9 ft and a min of 50pct to be 14 ft and longer

Width-location And Measuring Method:

8.000 inches specified

Measuring Method And Length:

8.000 feet random

Surface Condition Degree:

Rough-unsanded full length

Thickness-location And Measuring Method:

3.000 inches specified

Typical Wood Products Use:

Preservative treated high quality construction for above ground use where cleanliness and paintability not required

Service Usage:

For use above ground

Supplementary Features:

Unit of issue-bf

Specification Data:

81348-mm-I-751 government specification

Specification Or Standard:

lii table

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A173a0