NSN 5510-00-558-0429

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-558-0429

Treatment Type:

Preservative, tt-w-571

Preservative Solution Type:

Ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or pentachlorophenol in light petroleum solvent or pentachlorophenol in volatile solvent

Species-grade And Grading Association:

Douglas-fir, coastal no. 1 west coast lumber inspection bureau or douglas-fir, coastal no. 1 western wood products association or douglas-fir, coastal construction west coast lumber inspection bureau or douglas-fir, coastal construction western wood products association or douglas-fir, south, interior no. 1 west coast lumber inspection bureau or douglas-fir, south, interior no. 1 western wood products association or douglas-fir, south, interior construction west coast lumber inspection bureau or douglas-fir, south, interior construction western wood products association or hemlock, western no. 1 west coast lumber inspection bureau or hemlock, western no. 1 western wood products association or hemlock, western construction west coast lumber inspection bureau or hemlock, western construction western wood products association or larch no. 1 western wood products association or larch construction western wood products association or pine, eastern white no. 1 northeastern lumber manufacturers association or pine, eastern white no. 1 northern hardwood and pine manufacturers association or pine, eastern white construction northeastern lumber manufacturers association or pine, eastern white construction northern hardwood and pine manufacturers association or pine, idaho white no. 1 western wood products association or pine, idaho white construction western wood products association or pine, jack no. 1 northeastern lumber manufacturers association or pine, jack no. 1 northern hardwood and pine manufacturers association or pine, jack construction northeastern lumber manufacturers association or pine, jack construction northern hardwood and pine manufacturers association or pine, lodgepole no. 1 western wood products association or pine, lodgepole construction western wood products association or pine, ponderosa no. 1 western wood products association or pine, ponderosa construction western wood products association or pine, norway no. 1 northeastern lumber manufacturers association or pine, norway no. 1 northern hardwood and pine manufacturers association or pine, norway construction northeastern lumber manufacturers association or pine, norway construction northern hardwood and pine manufacturers association or pine, southern no. 1 southern pine inspection bureau or pine, southern construction southern pine inspection bureau or pine, sugar no. 1 western wood products association or pine, sugar construction western wood products association or redwood no. 1 redwood inspection service or redwood construction redwood inspection service

Random Length:

8 ft and loner with a maximum of 5pct to be 8-9 ft and a min of 50pct to be 14 ft and longer

Width-location And Measuring Method:

4.000 inches specified

Measuring Method And Length:

8.000 feet random

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

4.000 inches specified

Typical Wood Products Use:

Preservative treated high quality construction for above ground use for cleanliness and paintability

Service Usage:

For use above ground

Supplementary Features:

Unit of issue-bf

Specification Data:

81348-mm-l-751 government specification

Specification Or Standard: