# NSN 5510-00-558-0431

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-558-0431

# **Treatment Type:**

Preservative, tt-w-571

#### **Preservative Solution Type:**

Coal-tar creosote or creosote coal-tar solution or creosote petroleum solution or pentachlorophenol in heavy petroleum solvent

# **Species-grade And Grading Association:**

Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable no. 1 northern hardwood and pine manufacturers association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable no. 1 western wood products association or pine, southern no. 1 southern pine inspection bureau or redwood no. 1 redwood inspection service

### Random Length:

8 ft and longer with a maximum of 5 pct to be 8-9 ft and a min of 50 pct to be 14 ft and longer

#### Width-location And Measuring Method:

8.000 inches specified

### **Measuring Method And Length:**

8.000 feet random

#### **Surface Condition Degree:**

Rough-unsanded full length

#### **Thickness-location And Measuring Method:**

4.000 inches specified

# **Typical Wood Products Use:**

Preservative treated high quality construction for above ground use where cleanliness and paintability not required

# Service Usage:

Lumber and for use above ground

#### **Supplementary Features:**

See table i, tt-w-571 for acceptable species-unit of issue-board foot

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A173a0