Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-558-0432

## Treatment Type:

Preservative, tt-w-571

### Preservative Solution Type:

Coal-tar creosote or creosote coal-tar solution or creosote petroleum solution or pentachlorophenol in heavy petroleum solvent

## Species-grade And Grading Association:

Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable no. 1 northern hardwood and pine manufacturers association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable no. 1 western wood products association or pine, southern no. 1 southern pine inspection bureau or redwood no. 1 redwood inspection service

### Random Length:

8 ft and longer with a maximum of 5 pct to be 8-9 ft and a min of 50 pct to be 14 ft and longer

## Width-location And Measuring Method:

12.000 inches specified

### Measuring Method And Length:

8.000 feet random

### Surface Condition Degree:

Rough-unsanded full length

## Thickness-location And Measuring Method:

4.000 inches specified

## **Typical Wood Products Use:**

Preservative treated high quality construction for above ground use where cleanliness and paintability not required

### Service Usage:

Lumber and for use above ground

### Supplementary Features:

See table i, tt-w-571 for acceptable species-unit of issue-board foot

### Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No

### Fiig:

A173a0