Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-01-445-0900

Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii

Species-grade And Grading Association:

Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable construction northeastern lumber manufacturers association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable construction west coast lumber inspection bureau or any acceptable no. 1 western wood products association or any acceptable construction western wood products association or pine, southern no. 1 southern pine inspection bureau or pine, southern construction southern pine inspection bureau or redwood no. 1 redwood inspection service

Err Default:

Err default

Width-location And Measuring Method:

4.000 inches specified

Measuring Method And Length:

16.000 feet specified

Surface Condition Degree:

Surfaced four sides

Thickness-location And Measuring Method:

2.000 inches specified

Typical Wood Products Use:

Preservative treated high quality construction for above ground use for cleanliness and paintability

Service Usage:

Lumber and for use above ground

Supplementary Features:

Unit of issue-bf

Specification Data:

81348-mm-I-751 government specification

Specification Or Standard:

3 table

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A173a0