# NSN 5510-01-445-1016

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-01-445-1016

## Preservative Solution Type:

Acid copper chromate or ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii

## Species-grade And Grading Association:

Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable construction northeastern lumber manufacturers association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable construction west coast lumber inspection bureau or any acceptable no. 1 western wood products association or any acceptable construction western wood products association or pine, southern no. 1 southern pine inspection bureau or pine, southern construction southern pine inspection bureau or redwood no. 1 redwood inspection service

## Err Default:

Err default

## Width-location And Measuring Method:

4.000 inches specified

## Measuring Method And Length:

8.000 feet specified

## Surface Condition Degree:

Surfaced four sides

# **Thickness-location And Measuring Method:**

4.000 inches specified

# **Typical Wood Products Use:**

Preservative treated high quality construction for above ground use for cleanliness and paintability

## Service Usage:

Lumber and for use above ground

## **Supplementary Features:**

Unit of issue-bf

## **Specification Data:**

81348-mm-I-751 government specification

## **Specification Or Standard:**

3 table

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A173a0