## NSN 5530-00-128-5031

Construction Plywood - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5530-00-128-5031

Treatment Type: Fire retardant, mil-l-19140 Glue Type: Exterior Width-location And Measuring Method: 48.000 inches specified Measuring Method And Length: 8.000 feet specified Surface Condition Degree:
Exterior Width-location And Measuring Method: 48.000 inches specified Measuring Method And Length: 8.000 feet specified
Width-location And Measuring Method: 48.000 inches specified Measuring Method And Length: 8.000 feet specified
48.000 inches specified Measuring Method And Length: 8.000 feet specified
Measuring Method And Length: 8.000 feet specified
8.000 feet specified
Surface Condition Degree:
Regular sanded two sides
Thickness-location And Measuring Method:
0.375 inches specified
Typical Wood Products Use:
Exterior use utility panel for work buildings, box car and truck linings, containers and as base for exterior coatings for wall and roofs
Plywood Specificationies And Grade:
Softwood b-c exterior
Supplementary Features:
Typical use-for areas where high fire hazards exist, unit of issue sheet, no. Of plies-3
Specification Data:
81348-nn-p-530 government specification
Specification Or Standard:
B-c grade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A173a0