NSN 5640-00-237-4810

Thermal Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5640-00-237-4810

| Layer Quantity: 1 Fabrication Method: Expanded Material Density: Between 4.5 pounds per cubic foot and 8.5 pounds per cubic foot Flammability Rating: Not rated Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
|---|
| Expanded Material Density: Between 4.5 pounds per cubic foot and 8.5 pounds per cubic foot Flammability Rating: Not rated Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| Material Density: Between 4.5 pounds per cubic foot and 8.5 pounds per cubic foot Flammability Rating: Not rated Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| Between 4.5 pounds per cubic foot and 8.5 pounds per cubic foot Flammability Rating: Not rated Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| Flammability Rating: Not rated Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| Not rated Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| Insulation Thickness: 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| 0.500 inches Inside Diameter: 4.000 inches Length: 72.000 inches |
| Inside Diameter: 4.000 inches Length: 72.000 inches |
| 4.000 inches Length: 72.000 inches |
| Length: 72.000 inches |
| 72.000 inches |
| |
| |
| Design Form: |
| Full round |
| Tempurature Rating: |
| Between -20.0 degrees fahrenheit and 180.0 degrees fahrenheit |
| Flexibility: |
| Flexible |
| Material: |
| Plastic, foam, elastomeric |
| Material: |
| Plastic |
| Specification Or Standard: |
| T form |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A016a0 |
| Mil-std (military Standard): |
| , |