NSN 5820-01-381-4848

Radio Frequency Exciter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5820-01-381-4848

Overall Length:
22.600 inches
Overall Height:
7.000 inches
Overall Width:
19.000 inches
Vibration Resistance Range In Hertz:
+5.5/+55.0
Shock Resistance Rating In Gravitational Units:
1.5
Operating Tempurature Range:
+32.0/+122.0 degrees fahrenheit
Average Life Measurement:
Not rated
End Application:
5895-01-351-7334, an/gsq-23 (v) 2, command information link
Basic Shape Style:
Rectangular or square
Inclosure Type:
Partially enclosed
Operating Control Method:
Manual
Installation Design:
Rack
Circuit Construction Type:
Solid state
Frequency Per Channel:
1.6 megahertz operating channel and 30.0 megahertz operating channel
Frequency Adjustment Type:
Stepped
Individual Step Frequency:
10.0 hertz and 1.0 hertz
Average Power Rating Per Channel:
200.0 milliwatts output
Operating Ac Frequency In Hertz:
47.0 single voltage and 63.0 single voltage and 330.0 single voltage and 420.0 single voltage
External Ac Operating Voltage In Volts:
100.0 single voltage and 115.0 single voltage and 215.0 single voltage and 230.0 single voltage
Supplementary Features:
Tune power output: 100mw pep , 4 channel isb-ame-cw per the design concepts of mil-std-188-317
Shelf Life:
N/-

N/a

NSN 5820-01-381-4848

Radio Frequency Exciter - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200