

View Online at <https://aerobasegroup.com/nsn/5820-01-468-9663>

Overall Depth:

37.5 millimeters

Overall Height:

137.0 millimeters

Overall Width:

57.5 millimeters

Dc Voltage Rating:

7.5 volts

Frequency Rating:

Between 450.0 megahertz and 527.0 megahertz

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Included

Transmitter Channel Quantity:

16

Receiver Channel Quantity:

16

Power Output:

Between 4.000 watts and 5.000 watts

Special Features:

Meets or exceeds mil-std-810; also ip54 for sealing and tia/eia 603 for shock, vibration, dust and humidity; full bandsplit frequency separation in both the transmitter and receiver; frequency availability subject to country law and regulations; tri-colored led indicates rechargeable battery strength; switchable rf power level to conserve battery consumption; push button alarm; programmable channel spacing of 12.5/25 khz mode; can enable/disable repeater to talk to more than one unit, or talk unit to unit; internal voice operated transmission (vox); tight (filter out excessive noise) or normal squelch; complies with iso 9001 standard

Type/model Designation:

Gp328

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T199-d