

View Online at <https://aerobasegroup.com/nsn/5820-01-468-9663>

**Overall Depth:**

37.5 millimeters

**Overall Height:**

137.0 millimeters

**Overall Width:**

57.5 millimeters

**Dc Voltage Rating:**

7.5 volts

**Frequency Rating:**

Between 450.0 megahertz and 527.0 megahertz

**Electrical Power Source Relationship:**

Operating

**Internal Battery Accommodation:**

Included

**Transmitter Channel Quantity:**

16

**Receiver Channel Quantity:**

16

**Power Output:**

Between 4.000 watts and 5.000 watts

**Special Features:**

Meets or exceeds mil-std-810; also ip54 for sealing and tia/eia 603 for shock, vibration, dust and humidity; full bandsplit frequency separation in both the transmitter and receiver; frequency availability subject to country law and regulations; tri-colored led indicates rechargeable battery strength; switchable rf power level to conserve battery consumption; push button alarm; programmable channel spacing of 12.5/25 khz mode; can enable/disable repeater to talk to more than one unit, or talk unit to unit; internal voice operated transmission (vox); tight (filter out excessive noise) or normal squelch; complies with iso 9001 standard

**Type/model Designation:**

Gp328

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T199-d