

View Online at <https://aerobasegroup.com/nsn/5820-01-520-7245>

**Maximum Voltage Rating In Volts:**

120.0 ac

**Inclosure Type:**

Encased

**Maximumlength:**

9.000 inches

**Maximumwidth:**

7.000 inches

**Maximumheight:**

4.000 inches

**Product Name:**

Multi frequency tone remotes

**Special Features:**

Off white color; audio output to speaker 2 watts min, in compression, into 8 ohms with less than 3 pct distortion using supplied power pack; compression less than 3 db increase in output with 30 db increase beyond threshold of compression; line input adjustable minus 20 dbm min; frequency response porm 3 dbm from 300 to 3000 hz except at notch frequency; 1000 hz reference; signal to noise 50 db; line impedance 600 ohms/5000 ohms; line output adjustable plus 15 dbm max; factory set at 0 dbm; control tones security tone 2175 hz porm 0.01 pct at plus 10 dbm for 140 ms; function tones 1950-450 hz porm 0.01 pct at 0 dbm for 40 ms; monitor 2050 hz porm 0.01 pct at 0 dbm for 40 ms; transmit hold tone 2175 hz porm 0.01 pct minus 20 dbm for duration of ptt; connections 4 pin modular for handset; rj11 for desk microphone and phone pair; 4 wire simplex operation-separate tx and rx pairs

**Frequency In Hertz:**

60.0

**Functional Description:**

Provide control of up to 4 frequencies on a remotely located base station radio over a voice grade wire pair; use with ttp1-4w termination panel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A31700