

View Online at <https://aerobasegroup.com/nsn/5820-01-574-6665>

**Ac Voltage Rating:**

Between 12.0 volts and 120.0 volts

**Dc Voltage Rating:**

12.0 volts

**Frequency Rating:**

60.0 hertz

**Maximum Power Dissipation Rating:**

3.0 watts and 6.0 watts

**Furnished Items:**

Rf transceiver; connectors; led indicators; enclosure; 15 wireless touchpanels

**End Application:**

Transmitter group applications

**Component Document Origin:**

Industrial

**Document Source:**

3b4q0

**Accessory Identifying Number:**

Strfgwx specification no.

**Joint Electronics Type Designation System Item Name:**

Gateway control

**Electrical Power Source Relationship:**

Alternate operating

**Internal Battery Accommodation:**

Not included

**Installation Design:**

Transportable

**Receiver Frequency Rating:**

418.0 megahertz

**Transmitter Frequency Rating:**

418.0 megahertz

**Frequency Band Type And Quantity:**

2 receiving and 2 transmitting

**Frequency Channel Type And Quantity:**

15 receiving and 15 transmitting

**Emission Type:**

F9 receiving and f9 transmitting

**Product Name:**

Rf gateway control

**Phase:**

Single/three

**Special Features:**

Gateway is a rf transceiver for 2-way wireless touchpanels to communicate with the control system via the network; 50 feet indoors to 150 feet outdoors; can extend range by distributing multiple gateways-up to 16 per control system

**Err Default:**

Err default

**Supplementary Features:**

Dimensions without antenna-height 1.70inches; width 7.07inches; depth 6.32inches; weight 2.10pounds; steel black matte power coat finish; faceplate extruded aluminum, black matte power coat with polycarbonate level overlay

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T198-b