

View Online at <https://aerobasegroup.com/nsn/5820-01-574-6665>

Ac Voltage Rating:

Between 12.0 volts and 120.0 volts

Dc Voltage Rating:

12.0 volts

Frequency Rating:

60.0 hertz

Maximum Power Dissipation Rating:

3.0 watts and 6.0 watts

Furnished Items:

Rf transceiver; connectors; led indicators; enclosure; 15 wireless touchpanels

End Application:

Transmitter group applications

Component Document Origin:

Industrial

Document Source:

3b4q0

Accessory Identifying Number:

Strfgwx specification no.

Joint Electronics Type Designation System Item Name:

Gateway control

Electrical Power Source Relationship:

Alternate operating

Internal Battery Accommodation:

Not included

Installation Design:

Transportable

Receiver Frequency Rating:

418.0 megahertz

Transmitter Frequency Rating:

418.0 megahertz

Frequency Band Type And Quantity:

2 receiving and 2 transmitting

Frequency Channel Type And Quantity:

15 receiving and 15 transmitting

Emission Type:

F9 receiving and f9 transmitting

Product Name:

Rf gateway control

Phase:

Single/three

Special Features:

Gateway is a rf transceiver for 2-way wireless touchpanels to communicate with the control system via the network; 50 feet indoors to 150 feet outdoors; can extend range by distributing multiple gateways-up to 16 per control system

Err Default:

Err default

Supplementary Features:

Dimensions without antenna-height 1.70inches; width 7.07inches; depth 6.32inches; weight 2.10pounds; steel black matte power coat finish; faceplate extruded aluminum, black matte power coat with polycarbonate level overlay

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T198-b