

View Online at <https://aerobasegroup.com/nsn/5820-01-630-2494>

Storage Temperature Range:

-32.0 to 185.0 degrees fahrenheit

Document Source:

Oxyw1

Document Type:

Specification

Identification Designator:

Teleconference area

Model Number:

Cx3000 ip

Product Name:

Polycom cx3000 ip conference phone use for microsoft lync

Special Features:

Codec support: microsoft rtaudio; g.722.1; g.71 (narrowband, a-law and u-law) . User interface: display, 3.5', qvga tft 24 bit color graphical display, 320 x240 pixel, with unicode character capability. Led backlight with adjustable brightness. Backlight auto-dim when not in use. Connectivity: single ethernet 10/100 base-t with rj45 connector port, ieee 802.3f class single poe ethernet 10100 base-t, usb device port, type b female, 2 x extension mic ports.

Special Test Features:

Audio-speacer/mic: speaker frequency response, 200-7khz; speaker volume, at 1/2 meter peak volume: 85db; full duplex sepeakerphone, compliant with ieee 1329 type 1; acoustic echo cancellation; mic frequency response: 150-7khz; mic pickup: 12 f (3.5 m)

Supplementary Features:

Accessibility: high contrast ui graphic screen option (software); compatible with commercially-available tty adapter equipment.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23800