

View Online at <https://aerobasegroup.com/nsn/5821-00-665-0368>

Dc Voltage Rating:

28.0 volts

Maximum Power Dissipation Rating:

9.0 watts

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

Furnished Items:

Case dynamotor dynamotor unit jack box jack box mtg mtg rack radio control box radio receiver

Component Document Origin:

Government

Document Source:

80063

Document Type:

Maintenance instructions handbook

Document Identification:

An16-40 scr522-3

Component Document Page Number:

Section 1, page no. 1

Accessory Controlling Agency:

Sig

Accessory Identifying Number:

Cs-80-a or cs-80-c type no. And pe-94-a or pe-94-b or pe-94-c type no. And pe-98-a or pe-98-e or pe-98-f type no. And bc-629-am or bc-629-b type no. And bc-631-a or bc-631-b type no. And ft-488 type no. And ft-498 type no. And ft-244-a type no. And bc-602-a or bc-602-b or bc-602-d type no. And bc-624-a or bc-624-am or bc-624-c type no.

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Not included

Receiver Frequency Rating:

Between 100.0 megahertz and 156.0 megahertz

Transmitter Frequency Rating:

Between 100.0 megahertz and 156.0 megahertz

Frequency Channel Type And Quantity:

4 receiving and 4 transmitting

Emission Type:

A2 receiving and a2 transmitting and a3 receiving and a3 transmitting

Fsc Application Data:

Radio1except radioanavigation airborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T198-b