NSN 5825-00-337-3448

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5825-00-337-3448
Overall Length:
4.200 inches
Overall Height:
1.600 inches
Overall Width:
4.000 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
+0.0 to 70.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Open
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
399.9 megahertz 2nd operating channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
680.0 milliwatts output
Signal Voltage Rating Per Channel:
900.000 microvolts output
Overall Gain:
5.0 decibels
Impedance Rating Per Channel:

50.000 ohms 2nd operating channel

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, power front and receptacle, power rear

Connection Contact Type And Quantity:

5 receptacle, coaxial external and 1 receptacle, power external

NSN 5825-00-337-3448

Frequency Mixer Stage - Page 2 of 2



External Dc Operating Voltage In Volts	External	Dc O	perating	Voltage	In	Volts
--	----------	------	----------	---------	----	-------

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200