NSN 5825-01-407-8710

T198-b

Satellite Signals Navigation Set - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5825-01-407-8710 |
|---|
| Dc Voltage Rating: |
| 10.0 volts and 32.0 volts |
| Maximum Power Dissipation Rating: |
| 12.0 watts |
| Cubic Measure: |
| 306.797 cubic inches |
| End Application: |
| 6675-01-361-1355 |
| Electrical Power Source Relationship: |
| Alternate operating |
| Internal Battery Accommodation: |
| Not included |
| Receiver Frequency Rating: |
| Between 1227.6 megahertz and 1575.4 megahertz |
| Frequency Band Type And Quantity: |
| 1 receiving |
| Frequency Channel Type And Quantity: |
| 2 receiving |
| Emission Type: |
| +3g receiving |
| Special Features: |
| Submitted as receiver, radio. Geodetic quality accuracies internal data storage (6 mb); differential post processing accuracy (1 cm); |
| realtime differential accuracy (5m); tracks ca-code, and y-code. Velocity stationary (0); constant acceleration (36 kph); handheld (36 kph); |
| surface vehicle (90 kph); aircraft (999 kph). Horizontal position error stationary mode (12 m); constant acceleration (12 m); vertical position |
| error stationary mode (12 m); constant acceleration (15 m); surface vehicle (15 m); aircraft (16 m). 2d velocity error constant acceleration |
| (1.8 kph); surface vehicle (7.2 kph). Time mark (1 pps); error stationary mode (100 ns); constant acceleration (100 ns); surface vehicle |
| (100 ns); aircraft (100 ns). Have quick time error stationary mode (10 us); constant acceleration (10 us); surface vehicle (10 us); aircraft |
| (10 us). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |