

View Online at <https://aerobasegroup.com/nsn/5836-01-564-7601>

Case Material:

Fiberglass and plastic, polycarbonate

Environmental Protection:

Weatherproof and noncorrosive and dustproof

Fragility Factor:

Rugged

Maximum Voltage Rating In Volts:

198.0 ac or 264.0 ac

End Application:

Security monitoring

Inclosure Type:

Hermetically sealed

Current Rating In Amps:

2.0

Power Source:

External

Mounting Method:

Cabinet and wall

Features Provided:

Electrostatic sensitive

Maximumlength:

11.600 inches

Maximumheight:

6.500 inches

Intelligence Data Handling Capability:

Digital receiving automatic

Product Name:

Single channel onsite receiver/driver

Special Features:

Enclosure nema-4x ip66; rated voltage 230vac 50/60hz; pan/tilt output-4 function pan/tilt solide state drive with zero crossing turn-on 1adrive capability; lens output for zoom, focus, motorized iris 6vdc or 12vdc 100ma max; variable speed 6vdc setting 4vdc to 8vdc; variable speed 12 vdc setting 8vdc to 1chqja9.500

Frequency In Hertz:

50.0 or 60.0

Supplementary Features:

Emc requirements-ce immunity, ce emission class b, fcc class b, ices-003; safety-ce, ul, cul; wt. 15lbs; receiver/drivers are control data decoder units and motor drivers for pan/tilt/zoom lenses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A31700