## NSN 5841-01-466-8968

Gps Control Display Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5841-01-466-8968

Overall Length:
6.500 inches
Overall Height:
7.125 inches
Overall Width:
5.750 inches
Wattage Rating:
38.000 watts
Voltage In Volts And Current Type:
28.0 dc
Special Features:
Serial i/o - arinc 429 (2receive/2 transmit channels); rs-232/serial data bus; dual redundant multiplex bus per mil-std-1553; memory
includes, 1mb flash eeprom (aircraft/mission application software), 128kb uvprom-bit (hardware managers, boot strap software), 512 byte
ram, 64 byte eeprom-nonvolatile for data base variables; display 220 by 170 lines, nvg compatible; keyboard; dod validated ada language
(plm/86 application libraries available); embedded gps; gps tracks 5 channels/satellites; accuracy of 18 m sep with a velocity of 300 m/s,
acceleration of 2.5 g's; ttff 75 seconds (typical); gps has dual port memory and kyk-13 for loading of security keys, that interfaces with host
battery backup; convection cooling; hard, dzus mounting; predicted embedded gps receiver 10, 000 hour mtbf and predicted cdu-900
5800 hour mtbf, per mil-hdbk-217f with 70/30 mission profile mix
Functional Description:
Used to resolve navigation problems, aircraft
Relationship To Similar Equipment:
Identical software and receiver performance as dod miniature airborne gps receiver (magr)
Type/model Designation:
Cdu-900g
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli