## NSN 5845-01-515-8163

Sonar Sounding Set - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5845-01-515-8163

Dc Voltage Rating: Between 12.0 volts and 24.0 volts  Electrical Power Source Relationship: Operating Usage Design: Used as a fish finder  Transmitted Signal Frequency Rating: Between 50.0 hertz and 200.0 hertz  Power Output: 600.0 watts  Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screeolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable rangemarker and target simulator built-in; six levels of signal rejection level and noise limiter; 10-pin transducer/multisensor connection	
Electrical Power Source Relationship: Operating Usage Design: Used as a fish finder Transmitted Signal Frequency Rating: Between 50.0 hertz and 200.0 hertz Power Output: 600.0 watts Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screecolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Usage Design: Used as a fish finder Transmitted Signal Frequency Rating: Between 50.0 hertz and 200.0 hertz Power Output: 600.0 watts Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screecolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Used as a fish finder  Transmitted Signal Frequency Rating: Between 50.0 hertz and 200.0 hertz  Power Output: 600.0 watts  Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screecolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Used as a fish finder  Transmitted Signal Frequency Rating:  Between 50.0 hertz and 200.0 hertz  Power Output:  600.0 watts  Special Features:  8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screecolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Transmitted Signal Frequency Rating:  Between 50.0 hertz and 200.0 hertz  Power Output:  600.0 watts  Special Features:  8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screecolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Between 50.0 hertz and 200.0 hertz  Power Output:  600.0 watts  Special Features:  8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screecolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Power Output: 600.0 watts Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screcolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screcolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range.	
Special Features: 8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screcolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range.	
8 range scales to 4, 000 ft; audible/visual alarms; scope feature for rapid detection and id of fish and bottom conditions; selectable screcolors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
colors; alphanumeric displays of vessel speed and water temperature; range scale calibration in feet, fathoms or meters; variable range	
	een
marker and target simulator built in: giv levels of signal rejection level and noise limiter. 10 nin transducer/multiconger connection	је
marker and target simulator built-in, six levels or signal rejection level and noise limiter, no-pin transducer/multisensor connection	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
T212-g	