

View Online at <https://aerobasegroup.com/nsn/5855-00-832-7293>

Hole Diameter:

Between 3.341 inches and 3.351 inches

Width:

Between 0.057 inches and 0.067 inches

Overall Length:

Between 0.325 inches and 0.335 inches

Hole Or Slot Quantity:

2

Recess Diameter:

Between 3.526 inches and 3.536 inches

Recess Depth:

Between 0.160 inches and 0.180 inches

Thread Size:

3.656 in.-32

Depth:

Between 0.057 inches and 0.067 inches

End Application:

Cabinet, elec assembly cy-6255/grc and image intensifier assembly mx-8239/uv and power supply pp-179a/grd-1

Drive Type:

Slotted

Drive Facility Angular Spacing In Deg:

180.0

Guide Design:

Thread chamfer

Guide Location:

Edge opposite drive edge

Internal Annular Serration:

Not provided

Setscrew Notch:

Not provided

Material:

Aluminum alloy and aluminum alloy, qq-a-225/6, alloy 2024, t351

Material:

Aluminum alloy and aluminum alloy 2024

Special Test Features:

Finish anodize iaw mil-a-8525

Style Designator:

Recessed

Supplementary Features:

All fillets 0.005 to 0.010

Surface Treatment:

Anodized, mil-a-8625, type 2, class 2

Fsc Application Data:

Night vision equip. Emitted and reflected radiation

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T271-k