

View Online at <https://aerobasegroup.com/nsn/5855-00-832-7293>

**Hole Diameter:**

Between 3.341 inches and 3.351 inches

**Width:**

Between 0.057 inches and 0.067 inches

**Overall Length:**

Between 0.325 inches and 0.335 inches

**Hole Or Slot Quantity:**

2

**Recess Diameter:**

Between 3.526 inches and 3.536 inches

**Recess Depth:**

Between 0.160 inches and 0.180 inches

**Thread Size:**

3.656 in.-32

**Depth:**

Between 0.057 inches and 0.067 inches

**End Application:**

Cabinet, elec assembly cy-6255/grc and image intensifier assembly mx-8239/uv and power supply pp-179a/grd-1

**Drive Type:**

Slotted

**Drive Facility Angular Spacing In Deg:**

180.0

**Guide Design:**

Thread chamfer

**Guide Location:**

Edge opposite drive edge

**Internal Annular Serration:**

Not provided

**Setscrew Notch:**

Not provided

**Material:**

Aluminum alloy and aluminum alloy, qq-a-225/6, alloy 2024, t351

**Material:**

Aluminum alloy and aluminum alloy 2024

**Special Test Features:**

Finish anodize iaw mil-a-8525

**Style Designator:**

Recessed

**Supplementary Features:**

All fillets 0.005 to 0.010

**Surface Treatment:**

Anodized, mil-a-8625, type 2, class 2

**Fsc Application Data:**

Night vision equip. Emitted and reflected radiation

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T271-k