

View Online at <https://aerobasegroup.com/nsn/5865-01-455-4981>

**Case Material:**

Aluminum

**Maximum Voltage Rating In Volts:**

5.0 ac and 28.0 dc

**End Application:**

B-1b strategic aircraft and the towed decoy system

**Inclosure Type:**

Encased

**Current Rating In Amps:**

7.2

**Terminal Location:**

Back

**Power Source:**

External

**Mounting Method:**

Panel

**Maximum Wattage Rating In Watts:**

35.0

**Terminal Type And Quantity:**

33 screw

**Maximumlength:**

7.200 inches

**Maximumwidth:**

5.740 inches

**Maximumheight:**

7.110 inches

**Criticality Code Justification:**

Feat

**Special Features:**

Electrostatic sensitive device; is capable of second mil-std-1553 terminal operation, arinc 429 and rs 422 serial bus interface

**Functional Description:**

Provides the primary interface between the operator and the vcs; performs and displays operator initiated actions; reports operational status of the towed decoy system; reports results of the lru built-in test and provides mil-std-1553 interface; is a single lru containing a dedicated set of switches and indicators, direct access function (soft) keys and associated electronics; has green crt display with 8 lines of 22 characters each

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A31700