## NSN 5895-00-141-0264

Frequency Mixer Stage - Page 1 of 1



| Trequency mixer Stage - Tage Tor T   |
|--|
| View Online at https://aerobasegroup.com/nsn/5895-00-141-0264  |
| Average Life Measurement:  |
| Not rated  |
| Basic Shape Style:   |
| Rectangular or square  |
| Inclosure Type:  |
| Encased  |
| Operating Control Method:  |
| Automatic  |
| Installation Design:   |
| Mechanical   |
| Control Type:  |
| Remote   |
| Circuit Construction Type:   |
| Solid state  |
| Connection Type And Location:  |
| Integral cable w/power plug left side and receptacle, coaxial left side and receptacle, coaxial right side |
| Connection Contact Type And Quantity:  |
| 1 integral cable w/power plug external and 3 receptacle, coaxial external                                  |
| External Dc Operating Voltage In Volts:  |
| 15.0 single voltage  |
| Criticality Code Justification:  |
| Feat   |
| Special Features:  |
| Bias current selected  |
| Fsc Application Data:  |
| Miscellaneous communication equip.   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A32200   |
|  |
|  |