## NSN 5895-00-256-3536

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-256-3536

| Reliability Indicator:   |
|--|
| Not established  |
| Overall Length:  |
| 2.375 inches   |
| Overall Height:  |
| 0.656 inches   |
| Overall Width:   |
| 1.437 inches   |
| Environmental Protection:  |
| Vibration and shock resistant and fungus proof and salt spray resistant          |
| Operating Tempurature Range:   |
| +0.0/+65.0 degrees celsius   |
| Fragility Factor:  |
| Moderately rugged  |
| Average Life Measurement:  |
| Not rated  |
| Basic Shape Style:   |
| Rectangular or square  |
| Maximum Operating Altitude Rating:   |
| 6000.0 feet  |
| Inclosure Type:  |
| Encased  |
| Operating Control Method:  |
| Automatic  |
| Installation Design:   |
| Mechanical   |
| Control Type:  |
| Remote   |
| Circuit Construction Type:   |
| Solid state  |
| Frequency Per Channel:   |
| 1.0 gigahertz output channel and 12.2 gigahertz output channel                   |
| Frequency Adjustment Type:   |
| Continuous   |
| Connection Type And Location:  |
| Connector, plug left side and connector, plug right side and connector, plug top |
| Connection Contact Type And Quantity:  |
| 3 connector, plug external   |
| Fsc Application Data:  |
| Communication equipment, miscellaneous   |
| Shelf Life:  |
| N/a  |

## NSN 5895-00-256-3536

Frequency Mixer Stage - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200