NSN 5895-00-296-5119

Pulse Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-296-5119 **Overall Length:** 10.250 inches **Overall Height:** 9.875 inches **Overall Width:** 3.000 inches **Environmental Protection:** General purpose **Vibration Resistance Range In Hertz:** Not rated **Individual Section Quantity: Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range: Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased Installation Design: Mechanical **Circuit Construction Type:** Electron tube Frequency Per Channel: 1.0 hertz output channel **Frequency Adjustment Type:** Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** Not rated **Overall Gain:** Not rated

Impedance Rating Per Channel:

91.000 ohms output channel

NSN 5895-00-296-5119

Pulse Generator - Page 2 of 2



Pulse Duration Per Channel:
0.130 microseconds output channel
Polarity Per Channel:
Positive output channel
Pulse Repetition Rate Per Channel:
100.000 kilopulses per second 2nd input channel
Pulse Peak Amplitude Per Channel:
70.000 volts output channel
Output Wave Shape:
Pulse, trigger
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, power bottom
Operating Ac Frequency In Hertz:
60.0 single voltage
Connection Contact Type And Quantity:
16 receptacle, power external
External Dc Operating Voltage In Volts:
300.0 3rd voltage
External Ac Operating Voltage In Volts:
6.3 single voltage
Phase:
Single
Fsc Application Data:
Trainer, flight simulator
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A32200