## NSN 5895-00-371-1644

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-371-1644

Overall Length:
0.407 inches
Overall Diameter:
0.355 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-65.0 to 100.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Cylindrical
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
350.0 megahertz 2nd input channel
Attenuation In Decibels:
9.0
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Wire lead terminals bottom
Connection Contact Type And Quantity:
3 wire lead terminals external
Fsc Application Data:
Detector assembly, receiving set, sonobuoy bearing-range

## NSN 5895-00-371-1644

Frequency Mixer Stage - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200

