NSN 5895-00-471-0526

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-471-0526 **Overall Length: 5.968 inches Overall Height:** 2.937 inches **Overall Width:** 1.968 inches **Vibration Resistance Range In Hertz:** +5.0 to 25.0 **Shock Resistance Rating In Gravitational Units:** 25.0 **Operating Tempurature Range:** -0.0 to 50.0 degrees celsius **Average Life Measurement:** Indefinite **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Open Installation Design: Panel **Circuit Construction Type:** Solid state **Frequency Per Channel:** 41.9 megahertz operating channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: 25.000 millivolts output **Overall Gain:** Not rated Impedance Rating Per Channel: 50.000 ohms output channel **Maximum Continuous Operating Time In Hours:** Not rated **Shock Pulse Duration Time:** 11.0 milliseconds

Connection Type And Location:

Receptacle, power rear

NSN 5895-00-471-0526

Frequency Mixer Stage - Page 2 of 2



~ · · · · · · · · · · · ·	~	-		~
Connection	Contact	IVpe	Ana	Quantity:

9 receptacle, power external

External Dc Operating Voltage In Volts:

20.0 2nd voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200