NSN 5895-00-476-4853

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-476-4853 **Overall Length:** 19.400 inches **Overall Height:** 7.600 inches **Overall Width: 7.500** inches **Environmental Protection:** General purpose **Vibration Resistance Range In Hertz:** +70.0 to 500.0 **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -54.0 to 55.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** Am6518ur-80058 **Maximum Operating Altitude Rating:** 35000.0 feet **Inclosure Type:** Open **Operating Control Method:** Automatic Installation Design: Drawer **Control Type:** Remote **Circuit Construction Type:** Electron tube Frequency Per Channel: Not rated **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 1.0 watts output

Signal Voltage Rating Per Channel:

223.500 volts input

NSN 5895-00-476-4853

Radio Frequency Amplifier - Page 2 of 2



Overall Gain:	
40.0 decibels	
Impedance Rating Per Channel:	
50.000 ohms operating channel	
Distortion Type And Percent:	
1.0 amplitude	
Maximum Continuous Operating Time In Hours:	
Not rated	
Shock Pulse Duration Time:	
11.0 milliseconds	
Connection Type And Location:	
Receptacle, coaxial rear	
Operating Ac Frequency In Hertz:	
400.0 single voltage	
Connection Contact Type And Quantity:	
1 receptacle, coaxial external	
External Ac Operating Voltage In Volts:	
208.0 single voltage	
Phase:	
Three	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Filg:	
A32200	