Frequency Shift Converter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-503-2600

Inclosure Material:
Aluminum
Overall Length:
19.000 inches
Overall Height:
8.750 inches
Overall Width:
17.000 inches
Surface Luster:
Matte
Basic Shape Style:
Rectangular or square
Identification Designator:
Cv116urr-80058
Inclosure Type:
Installation Design:
Rack
Circuit Construction Type:
Electron tube
Frequency Per Channel:
29.300 kilohertz 1st output channel
Average Power Rating Per Channel:
200.0 watts output
Signal Voltage Rating Per Channel: 100.000 microvolts input
Impedance Rating Per Channel:
500.000 ohms input channel
Indicator Device Type And Quantity:
1 light and 4 meter
Connection Type And Location:
Receptacle, power rear
Operating Ac Frequency In Hertz:
60.0 single voltage
External Ac Operating Voltage In Volts:
115.0 single voltage
Phase:
Single
Functional Description:
Provides dual diversity convesion of frequency shift signals to dc pulses for operating teletypewriter machines
Color:

Gray

Frequency Shift Converter - Page 2 of 2



Fsc Application Data:

Teletypewriter printer

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200