## NSN 5895-00-503-2600

Frequency Shift Converter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-503-2600 **Inclosure Material:** Aluminum **Overall Length:** 19.000 inches **Overall Height:** 8.750 inches **Overall Width:** 17.000 inches **Surface Luster:** Matte **Basic Shape Style:** Rectangular or square **Identification Designator:** Cv116urr-80058 **Inclosure Type:** Encased Installation Design: Rack **Circuit Construction Type:** Electron tube **Frequency Per Channel:** 29.300 kilohertz 1st output channel **Average Power Rating Per Channel:** 200.0 watts output Signal Voltage Rating Per Channel: 100.000 microvolts input Impedance Rating Per Channel: 500.000 ohms input channel **Indicator Device Type And Quantity:** 1 light and 4 meter **Connection Type And Location:** Receptacle, power rear **Operating Ac Frequency In Hertz:** 60.0 single voltage **External Ac Operating Voltage In Volts:** 115.0 single voltage Phase: Single **Functional Description:** Provides dual diversity convesion of frequency shift signals to dc pulses for operating teletypewriter machines

Color: Gray

## NSN 5895-00-503-2600

Frequency Shift Converter - Page 2 of 2



Fsc Application Data	Fsc A	oplicatio	n Data:
----------------------	-------	-----------	---------

Teletypewriter printer

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200