## NSN 5895-00-545-7223

Signal Comparator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-00-545-7223

Overall Length:
24.250 inches
Overall Height:
20.000 inches
Overall Width:
24.000 inches
Ac Voltage Rating:
115.0 volts
Dc Voltage Rating:
24.0 volts 2nd operating power rqmt
Frequency Rating:
400.0 hertz
End Application:
Radio set, an/tps-1g
Joint Electronics Type Designation System Item Name:
Comparator, signal
Joint Electronics Type Designation System Item Type Number:
Cm-36/tps-1d
Electrical Power Source Relationship:
Operating
Internal Battery Accommodation:
Not included 1st operating power rqmt
Indicator Type:
Meter
Input Impedance Rating:
Not rated
Output Impedance Rating:
Not rated
Operating Frequency:
60.0 megahertz
Unpackaged Unit Weight:
200.000 pounds
External Control:
Operation selector switch, test selector switch
Phase:
Single
Functional Description:
Unit receives 60 mc echo signals from the 60 mc preamplifier in the receiver-transmitter; also receives 60 mc transmitter signals from the
coho mixer for mti sync and generates mti triggers which are delivered to the modulator; modified to following extent: modified chassis an
one if strip for gated mti: an additional basic adjustment control for mti gate balance, has been added to panel; hinged cover necessarily w

**Supplementary Features:** 

Aluminum case, usmc green finish

Fee Application Data:

coho mixer for mti sync and generates mti triggers which are delivered to the modulator; modified to following extent: modified chassis and one if strip for gated mti; an additional basic adjustment control for mti gate balance, has been added to panel; hinged cover necessarily will change; a lightweight, hermetically sealed quartz delay line, w/mtg provided replaces the mercury delay line; filament transformer rating increased; contains all circuitry necessary for gated mti

## NSN 5895-00-545-7223

Signal Comparator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

T263-c